



## VTQ Mentor Vision - X

Auflösung:	bis zu 1920 x 1080 px	Resolution:	up to 1920 x 1080 px
Schwenkbereich:	320°	Tilt range:	320°
Neigebereich:	+/-20°	Pan range:	+/-20°

### Eigenschaften:

- » Lichtstarker 1/2" Sensor
- » 36-fach optischer Zoom
- » hervorragend geeignet bei Nacht
- » kompakte Bauform
- » Tag / Nachtschaltung mit Schwenkfilter
- » sehr präzise Steuerung
- » Befestigung über Gewindebolzen an der Unterseite
- » geeignet für den Innenbereich oder geschützt unter wetterfesten Behältnissen

### Features:

- » low light 1/2" sensor
- » 36 x optical zoom
- » excellent at night
- » compact construction
- » Day / Night switch with cut filter
- » very precise control
- » Fastening via threaded bolts on the underside
- » suitable for indoor use or protected under weatherproof containers

**VTQ Mentor Vision - X**  
7500 850070

**VTQ Mentor Vision - X**  
7500 850070

### TECHNISCHE DATEN // TECHNICAL DETAILS

Auflösung / Resolution	.....bis zu // up to 1920 x 1080p@60fps
Bildsensor / Image Sensor	.....Sony IMX385LQR 1/2"
Total Pixel	.....1945 x 1097 approx. 2.13M
Scansystem / Scanning System	.....Internal
Min. Illumination	.....Color: 0.05 lux@50IRE F1.5; .....S/W: 0,01lux@50IRE F1.5
S/N ratio	.....mehr als / more than 50dB(AGC off)
Objektiv / Lens Type	.....X36 Day & Night zoom lens
Brennweite / Focal length	.....W 6.0mm/F1.5 ~ T 210/F4.8mm
Blickwinkel / Angle of view	.....Wide: H 56.5° ~ V 33.6° .....Tele: H 2.3° ~ V 2.0°
Verschlusszeit / Shutter Speed	.....1/10 - 1/30.000
WDR/BLC/HLC	.....off/WDR/BLC
Rauschunterdrückung / Noise reduction 2D-NR, 3D-NR	.....Auto/Day/Night
Day/Night	.....Auto/Day/Night
Weißabgleich / White Balance	.....ATW-Indoor/Outdoor, manuell
Spiegel / Mirror	.....Off/H/V/H&V

### NETZWERK // NETWORK

Protokoll / Protocol	.....TCP/IP, UDP, IPv4/v6, .....HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, .....DHCP, ARP, Zeroconf
Streaming	.....Simultaneously H.265/H.264 .....and MJPEG (Multi Streaming) or .....Independent Frame rate .....and Bandwidth Control, VBR/CBR Mode
Management	.....API, ONVIF Profile S Compliant
Komprimierung / Compression	.....H.265 Main profile, .....H.264 (High, Main, Base line profile), MJPEG
Bildrate / Frame rate	.....bis zu // up to 60fps@1920 x 1080p

### ABMESSUNGEN // DIMENSIONS INTERFACEBOX

Abmessungen / Dimensions Interfacebox	.....123 x 68 x 35 mm
Anschluss / Connector	.....RJ45 (10/100BASE-T)
Stromversorgung / Power supply	.....12V DC/max. 0.4A, Lemobuchse
Verbindungskabel Kamera-Interfacebox / Connection cable Camera-Interfacebox	.....1m, fest
Gewicht / Weight	.....Interfacebox: 220g .....Kamera / Camera: 820g

