



einstellbarer Neigungswinkel  
adjustable inclination angle

## VTQ TFT-5000

Der VTQ TFT-5000 ist ein hochauflösender TFT-Monitor in einem robusten Metallgehäuse. Das moderne schlanke Gehäuse verfügt über einen Standfuß.

Der Monitor unterstützt den VESA-Standard und kann unter Verwendung entsprechenden Zubehörs platzsparend an der Wand montiert werden.

### EIGENSCHAFTEN

- » 12,7cm (5") TFT-Display
- » hohe Auflösung 640 x 480 Pixel
- » Metallgehäuse mit Schutzglas
- » inkl. IR-Fernbedienung
- » verschiedene Videoeingänge
- » einstellbarer Neigungswinkel
- » unterstützt Bildspiegelung (horizontal/vertikal)
- » ideal für mobile Anwendungen
- » LED Backlight Technologie

## VTQ TFT-5000

*The VTQ TFT-5000 is a high resolution LCD monitor housed in a robust metal casing. The unit boasts a contemporary, slim line design including desktop bracket.*

*To conserve workspace the monitor can be easily wall mounted using industry standard VESA mounting equipment.*

### FEATURES

- » 12.7cm (5") Screen
- » High Resolution 640 x 480
- » Metal housed with tempered protective glass
- » Incl. IR remote control
- » Multiple video input types
- » Inclination angle adjustable
- » Support Mirror Image (horizontal/vertical)
- » Perfect for mobile applications
- » LED backlight technology

### TECHNISCHE DATEN // TECHNICAL DETAILS

LCD Panel	12.7cm (5")
	Diagonal LED backlight
Auflösung / Resolution	640 x 480 (HxV)
Aktive Bildfläche / Active display area	101.56 x 76.18mm (HxV)
Helligkeit / Brightness	250cd/m <sup>2</sup>
Pixelabmessungen / Pixel dimensions	0.0529 x 0.1587mm (HxV)
Kontrastverhältnis / Contrast ratio	500:1 (typ.)
Reaktionszeit / Response time	8ms
Blickwinkel / Viewing angle	130° / 110° (H+V)
Farben / Colours	16.2 Millions
Synchronisation	TTL positiv/negative
Frequenzen / Frequencies	30-80kHz (H) 50-75Hz (V)
Farbtemperatur / Colour temperature	... einstellbar / adjustable (9300/6500/5800/User)
Videonorm / Video standard	NTSC / PAL
Seitenverhältnis / Aspect ratio	4:3
Lautsprecher / Speakers	Nein / No
OSD	Ja / Yes
Lebensdauer LED / LED Lamp Lifetime	30.000h
LCD Schutzglas / LCD Protection glass	Ja / Yes
Stumm / Mute	Ja / Yes
Videoeingang / Video input	2x BNC
Audioeingang / Audio input	Nein / No
DC-Eingang / Power interface	2.1/5.5mm
Stromversorgung / Power supply	12V DC
Stromaufnahme / Power consumption	.. 350mA (typ.)
Zertifizierung / Certification	CE / FCC / RoHS
Wandmontage / Wall Mount	VESA (56x56mm)
Abmessungen / Dimensions	150 x 120 x 30mm
Gewicht / Weight	800g

VTQ TFT-5000

7500 856005

VTQ TFT-5000

7500 850005



einstellbarer Neigungswinkel  
adjustable inclination angle

## VTQ TFT-8000

Der VTQ TFT-8000 ist ein hochauflösender TFT-Monitor in einem robusten Metallgehäuse. Das moderne schlanke Gehäuse verfügt über einen Standfuß und seitliche Steuerelemente.

Der Monitor unterstützt den VESA-Standard und kann unter Verwendung entsprechenden Zubehörs platzsparend an der Wand montiert werden.

### EIGENSCHAFTEN

- » 20,32cm (8") TFT-Display
- » hohe Auflösung 800 x 600 Pixel
- » Metallgehäuse mit Schutzglas
- » verschiedene Videoeingänge
- » seitliche Steuerelemente
- » einstellbarer Neigungswinkel
- » unterstützt Bildspiegelung (horizontal/vertikal)
- » ideal für mobile Anwendungen
- » LED Backlight Technologie

## VTQ TFT-8000

*The VTQ TFT-8000 is a high resolution LCD monitor housed in a robust metal casing. The unit boasts a contemporary, slim line design including discreet, side mounted controls.*

*To conserve workspace the monitor can be easily wall mounted using industry standard VESA mounting equipment.*

### FEATURES

- » 20.32cm (8") Screen
- » High Resolution 800 x 600
- » Metal housed with tempered protection glass
- » Multiple video input types
- » Discreet, side mounted controls
- » Inclination angle adjustable
- » Support Mirror Image (horizontal/vertical)
- » Perfect for mobile applications
- » LED backlight technology

### TECHNISCHE DATEN // TECHNICAL DETAILS

LCD Panel	20.32cm (8")
	Diagonal LED backlight
Auflösung / Resolution	800 x 600 (HxV)
Aktive Bildfläche / Active display area	162 x 122mm (HxV)
Helligkeit / Brightness	350cd/m <sup>2</sup>
Pixelabmessungen / Pixel dimensions	0.0675 x 0.2025mm (HxV)
Kontrastverhältnis / Contrast ratio	500:1 (typ.)
Reaktionszeit / Response time	8ms
Blickwinkel / Viewing angle	140° / 130° (H+V)
Farben / Colours	16.2 Millions
Synchronisation	TTL positiv/negative
Frequenzen / Frequencies	30-80kHz (H) 50-75Hz (V)
Farbtemperatur / Colour temperature	... einstellbar / adjustable (9300/6500/5800/User)
Videoform / Video standard	NTSC / PAL
Seitenverhältnis / Aspect ratio	4:3
VGA-Frequenzkorrektur / VGA Frequency Correction	Ja / Yes
Lautsprecher / Speakers	Nein / No
OSD	Ja / Yes
Lebensdauer LED / LED Lamp Lifetime	30.000h
LCD Schutzglas / LCD Protection glass	Ja / Yes
Stumm / Mute	Ja / Yes
Auto-Einstellung / Auto adjustment	Ja / Yes
Videoeingang / Video input	1x VGA, 2x BNC
Audioeingang / Audio input	Nein / No
DC-Eingang / Power interface	2.1/5.5mm
Stromversorgung / Power supply	12V DC
Stromaufnahme / Power consumption	.. 450mA (typ.)
Zertifizierung / Certification	CE / FCC / RoHS
Wandmontage / Wall Mount	VESA (75x75mm)
Abmessungen / Dimensions	205 x 175 x 80mm
Gewicht / Weight	1400g

VTQ TFT-8000

7500 856006

VTQ TFT-8000

7500 850006



Seitenansicht / Side view

## VTQ TFT-1040 II

Der VTQ TFT-1040 II ist ein hochauflösender TFT-Monitor in einem robusten Metalgehäuse. Das moderne schlanke Gehäuse verfügt über einen Standfuß und seitliche Steuerelemente.

Der Monitor unterstützt den VESA-Standard und kann unter Verwendung entsprechenden Zubehörs platzsparend an der Wand montiert werden.

### EIGENSCHAFTEN

- » 26,42cm (10,4") TFT-Display
- » hohe Auflösung 800 x 600 Pixel
- » Metallgehäuse mit Schutzglas
- » verschiedene Videoeingänge
- » Loop-through Videoausgang
- » seitliche Steuerelemente
- » inkl. Standfuß
- » unterstützt Bildspiegelung (horizontal/vertikal)
- » ideal für mobile Anwendungen
- » LED Backlight Technologie

## VTQ TFT-1040 II

*The VTQ TFT-1040-II is a high resolution monitor housed in a robust metal casing. The unit boasts a contemporary, super slim line design including discreet, side mounted controls.*

*To conserve workspace the monitor can be easily wall mounted using industry standard VESA mounting equipment.*

### FEATURES

- » 26.42cm (10.4") Screen
- » High Resolution 800 x 600
- » Metal housed with tempered protection glass
- » Multiple video input types
- » BNC loop through
- » Discreet, side mounted controls
- » Incl. supporting stand
- » Support Mirror Image (horizontal/vertical)
- » Perfect for mobile applications
- » LED backlight technology

### TECHNISCHE DATEN // TECHNICAL DETAILS

LCD Panel	26.42cm (10.4")
	Diagonal LED backlight
Auflösung / Resolution	800 x 600 (HxV)
Aktive Bildfläche / Active display area	211.2 x 158.4mm (HxV)
Helligkeit / Brightness	300cd/m <sup>2</sup>
Pixelabmessungen / Pixel dimensions	0.33 x 0.33mm (HxV)
Kontrastverhältnis / Contrast ratio	500:1 (typ.)
Reaktionszeit / Response time	8ms
Blickwinkel / Viewing angle	150° / 110° (H+V)
Farben / Colours	16.2 Millions
Frequenzen / Frequencies	30-80kHz (H) 50-75Hz (V)
Farbtemperatur / Colour temperature	... einstellbar / adjustable (9300/6500/5800/User)
Videonorm / Video standard	NTSC / PAL
Seitenverhältnis / Aspect ratio	4:3
VGA-Frequenzkorrektur / VGA Frequency Correction	Ja / Yes
Lautsprecher / Speakers	Nein / No
OSD	Ja / Yes
Lebensdauer LED / LED Lamp Lifetime	10.000h
LCD Schutzglas / LCD Protection glass	Ja / Yes
Stumm / Mute	Ja / Yes
Auto-Einstellung / Auto adjustment	Ja / Yes
Videoeingang / Video input	1x VGA, 1x BNC
Videoausgang / Video output	1x BNC
Audioeingang / Audio input	Nein / No
DC-Eingang / Power interface	2.1/5.5mm
Stromversorgung / Power supply	12V DC
Stromaufnahme / Power consumption	.. 600mA (typ.)
Zertifizierung / Certification	CE / FCC / RoHS
Wandmontage / Wall Mount	VESA (75x75mm)
Abmessungen / Dimensions	270 x 220 x 45mm
Gewicht / Weight	1700g

VTQ TFT-1040 II

7500 856007

VTQ TFT-1040 II

7500 850007



VTQ TFT-15000



VTQ TFT-15000 Protected

## VTQ TFT-15000

Der VTQ TFT-15000 ist ein hochauflösender TFT-Monitor, wahlweise mit Plastikgehäuse oder in einem robusten Metallgehäuse mit Schutzglas. Das moderne schlanke Gehäuse verfügt über seitliche Steuerelemente.

Der Monitor unterstützt den VESA-Standard und kann unter Verwendung entsprechenden Zubehörs platzsparend an der Wand montiert werden. Der ausklappbare Standfuß erlaubt die Anpassung des Neigungswinkels.

### EIGENSCHAFTEN

- » 38,1cm (15") TFT-Display
- » hohe Auflösung 1024 x 768 Pixel
- » Metallgehäuse mit Schutzglas (nur Protected)
- » verschiedene Videoeingänge
- » Stereo Audio
- » 12V Spannungsversorgung
- » seitliche Steuerelemente
- » Loop-through Videoausgang
- » VESA-Mount
- » ideal für mobile Anwendungen
- » LED Backlight Technologie

## VTQ TFT-15000

*The VTQ TFT-15000 is a high resolution LCD monitor housed in a robust plastic casing or in a metal casing with tempered protection glass. The unit boasts a contemporary, slim line design including discreet, side mounted controls.*

*To conserve workspace the monitor can be easily wall mounted using industry standard VESA mounting equipment. Foldable stand add flexibility to your viewing preferences.*

### FEATURES

- » 38.1cm (15") Screen
- » High Resolution 1024 x 768
- » Metal housed with tempered protection glass (Protected only)
- » Multiple video input types
- » Stereo audio
- » Voltage: 12V DC
- » Discreet, side mounted controls
- » BNC loop through
- » VESA mount
- » Perfect for mobile applications
- » LED backlight technology

### TECHNISCHE DATEN // TECHNICAL DETAILS

LCD Panel	38.1cm (15")
	Diagonal LED backlight
Auflösung / Resolution	1024 x 768 (HxV)
Aktive Bildfläche / Active display area	304.10 x 228.10mm (HxV)
Helligkeit / Brightness	250cd/m <sup>2</sup>
Pixelabmessungen / Pixel dimensions	0.297 x 0.297mm (HxV)
Kontrastverhältnis / Contrast ratio	500:1 (typ.)
Reaktionszeit / Response time	5ms
Blickwinkel / Viewing angle	170° (H+V)
Farben / Colours	16.7 Millions
Frequenzen / Frequencies	30-80kHz (H) 50-75Hz (V)
Farbtemperatur / Colour temperature	... einstellbar / adjustable (9300/6500/5800/User)
Videonorm / Video standard	NTSC / PAL
Seitenverhältnis / Aspect ratio	4:3
VGA-Frequenzkorrektur / VGA Frequency Correction	Ja / Yes
Lautsprecher / Speakers	R + L
OSD	Ja / Yes
LCD Schutzglas / LCD Protection glass	Standard ..... Nein / No Protected ..... Ja / Yes
Stumm / Mute	Ja / Yes
Auto-Einstellung / Auto adjustment	Ja / Yes
Videoeingang / Video input	1x VGA, 2x BNC, 1x HDMI
Videoausgang / Video output	1x BNC
Audioeingang / Audio input	1x RCA
DC-Eingang / Power interface	2.1/5.5mm
Stromversorgung / Power supply	12V DC
Stromaufnahme / Power consumption	..... 1.4A (typ.)
Zertifizierung / Certification	CE / FCC / RoHS
Wandmontage / Wall Mount	..... VESA (100x100mm)
Abmessungen / Dimensions	Standard ..... 355 x 260 x 50mm Protected ..... 355 x 260 x 45mm
Gewicht / Weight	Standard ..... 2800g Protected ..... 3360g

VTQ TFT-15000 7500 856008  
VTQ TFT-15000 Protected 7500 856032

VTQ TFT-15000 7500 850008  
VTQ TFT-15000 Protected 7500 850032



Anschlüsse / Connectors  
(VTQ TFT-15000)





## VTQ TFT-HD1330

Der VTQ TFT-1330 ist ein hochauflösender Full-HD TFT-Monitor in einem robusten Metallgehäuse mit Schutzglas. Das moderne schlanke Gehäuse verfügt über seitliche Steuerelemente.

Der Monitor unterstützt den VESA-Standard und kann unter Verwendung entsprechenden Zubehörs platzsparend an der Wand montiert werden. Der ausklappbare Standfuß erlaubt die Anpassung des Neigungswinkels.

### EIGENSCHAFTEN

- » 33,78cm (13,3") TFT-Display
- » Full-HD Auflösung 1920 x 1080 Pixel
- » extrem hohe Detailschärfe
- » Metallgehäuse mit Schutzglas
- » verschiedene Videoeingänge
- » Stereo Audio
- » 12V Spannungsversorgung
- » VESA-Mount
- » ideal für mobile Anwendungen
- » LED Backlight Technologie

### OPTIONALES ZUBEHÖR

- » HD-SDI / HDMI-Konverter

## VTQ TFT-HD1330

*The VTQ TFT-HD1330 is a high resolution Full-HD LCD monitor housed in a robust metal casing with tempered protection glass. The unit boasts a contemporary, slim line design including discreet, side mounted controls.*

*To conserve workspace the monitor can be easily wall mounted using industry standard VESA mounting equipment. Foldable stand add flexibility to your viewing preferences.*

### FEATURES

- » 33.78cm (13.3") Screen
- » Full-HD High Resolution 1920 x 1080
- » extreme high detail sharpness
- » Metal housed with tempered protection glass
- » Multiple video input types
- » Stereo audio
- » Voltage: 12V DC
- » VESA mount
- » Perfect for mobile applications
- » LED backlight technology

### OPTIONAL ACCESSORIES

- » HD-SDI / HDMI Converter

### TECHNISCHE DATEN // TECHNICAL DETAILS

LCD Panel	38.1cm (13.3")
	Diagonal LED backlight
Auflösung / Resolution	1920 x 1080 (HxV)
Aktive Bildfläche / Active display area	293.76 x 165.24mm (HxV)
Helligkeit / Brightness	350cd/m <sup>2</sup>
Pixelabmessungen / Pixel dimensions	0.1529 x 0.1529mm (HxV)
Kontrastverhältnis / Contrast ratio	600:1 (typ.)
Reaktionszeit / Response time	8ms
Blickwinkel / Viewing angle	170° (H+V)
Farben / Colours	16.7 Millions
Frequenzen / Frequencies	30-80kHz (H) 50-75Hz (V)
Farbtemperatur / Colour temperature	... einstellbar / adjustable (9300/6500/5800/User)
Videonorm / Video standard	NTSC / PAL
Seitenverhältnis / Aspect ratio	16:10
VGA-Frequenzkorrektur / VGA Frequency Correction	Ja / Yes
Lautsprecher / Speakers	R + L
OSD	Ja / Yes
LCD Schutzglas / LCD Protection glass	Ja / Yes
Stumm / Mute	Ja / Yes
Auto-Einstellung / Auto adjustment	Ja / Yes
Videoeingang / Video input	1x VGA, 1x HDMI
Audioeingang / Audio input	1x RCA
Audioausgang / Audio output	1x RCA
DC-Eingang / Power interface	2.1/5.5mm
Stromversorgung / Power supply	12V DC
Stromaufnahme / Power consumption	1.4A (typ.)
Zertifizierung / Certification	CE / FCC / RoHS
Wandmontage / Wall Mount	VESA
Abmessungen / Dimensions	305 x 188 x 28mm
Gewicht / Weight	260g

VTQ TFT-HD1330

7500 856035

VTQ TFT-HD1330

7500 850035